



HEAVY-DUTY EYEBATH WITH FLEXIBLE EYEWASH

MODEL: EB2C

Ideal for any environment and fully compliant with ANSI Z356.1-2014 and EN15154 standards, this heavy-duty eyebath requires mains water pressure of 2-3 bar and is operated by lifting the lid. The unit is completely corrosion resistant and suitable for hazardous or non-hazardous environments. Supplied with micron filter to remove impurities and flow control.

KEY FEATURES

- Comes with 5 micron filter
- Highly visible, heavy-duty
- Stainless steel pipework & valve
- Manufactured in house, in the UK



OPERATING CONDITIONS

RECOMMENDED MAINS WATER PRESSURE 2 - 3 bar
TEMPERATURE -5°C to +40°C

TECHNICAL DETAILS

INLET CONNECTION ½" BSPM (*flanged options available*)
EYEBATH DRAIN OUTLET CONNECTION 40mm PVC-U
EYEBATH FLOW RATE 23lpm
EYEWASH FLOW RATE Min 1.5lpm
EYEBATH OPERATION Lift lid (*foot operation as option*)
EYEBATH FILTER 5 micron
EYEWASH OPERATION Hand lever

MATERIAL DETAILS

PIPEWORK 316 stainless steel
OPERATING VALVES 316 stainless steel
HINGES 316 stainless steel
LID & BASE Yellow GRP
HANDLE Black plastic
FLEXIBLE EYEWASH Blue nylon coil
NOZZLES Aerated - chrome plated

www.aqua-safety.com



Aqua Safety Showers International Ltd,
Redgate Road, South Lancashire Industrial Estate,
Ashton-in-Makerfield, Wigan, WN4 8DT. UK




sales@aqua-safety.com



+44 (0) 1942 318096

VAT No: 259714570
Registration No: 10427026

OPTIONAL EXTRAS



TECHNICAL DRAWINGS

